

LEDLENSER

INDUSTRIAL LIGHTS







	i6R
	Maxmin.
Light Output (lm)	120-10
Beam Distance (m)	100-30
Run Time (h)	25-4
Rechargeable	•
Item no. (BOX)	880318

i7DR	
Maxmin.	
220-25	
180-60	
30-4	
•	
880321	

	iH6R	
N	/axmin.	
	200-5	
	120-20	
	40-2	
	•	
	880388	

SAFETY LIGHTS







	EX4	
Light Output (lm)	50	
Beam Distance (m)	35	
Run Time (h)	7	
Rechargeable	-	
Item no. (BOX)	880428	

EXH8R	
Maxmin.	
200-45	
130-60	
45-10	
•	
880432	

iLH8R	
Maxmin.	
300-50	
160-70	
40-7	
*	
990/27	



A place in which an explosive atmosphere consisting of a mixture with air of dangerous substances in the form of gas, vapor or a cloud of combustible dust is **continuously present** for long periods or frequently (e.g. in gas tanks or grain elevators).



Working areas in which explosive atmospheres in the form of flammable gases, vapors or dust clouds prevail occasionally.



Working areas in which explosive atmospheres in the form of flammable gases, vapors or dust clouds (e.g. in case of a gas leak) usually do not prevail / prevail only for a short time.

Contact information:

 $www.ledlenserusa.com \mid Instagram @ ledlenserusa \mid facebook.com / Ledlenser Americas$